



PREPASTED NON-WOVEN DESIGN2WALL SOL 225

satin 2513, 225 g/m²

High quality wallpaper coated with a satin finish specifically for solvent inks, providing outstanding colour brilliance and scratch resistance. Thanks to the paste backcoating, activated by wetting it with water, it can be hung with no additional protection needed.

Advantages

- Backcoated with a permanent waterbased paste guaranting long-lasting use
- High opacity for good coverage, covering small hairline cracks
- PVC-free
- FSC® certified
- Quick dry
- Wide colour gamut and good colour reproduction
- The inkjet coating has a smooth surface with satin finish
- Both coating and print are water-resistant – no liquid lamination required
- High dimensional stability and wet strength, allowing "pre & post" paste cutting



Technologies



Properties



General tips

To maintain the high quality of this wallpaper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

Physical data

Name	Value	Norm
Weight [g/m ²]	225	ISO 536
Thickness (paper) [µm]	330	ISO 534
Whiteness, CIE D65/2°	65	ISO 11476
Opacity [%]	90	ISO 2471
Chromaticity (D65/10°)	L* 96 a* -0.3 b* 5	DIN 6174