

#### Specifications

XpertJet		XPJ-461UF	XPJ 661UF
Printing system	1	On-demand pie	ezo drive system
Set media	Size (W×D)	483mm (19") ×329mm (12.95")	483mm (19") ×594mm (23.4")
	Height	up to 70mm (2.75") [with standard table] / up to 150mm (5.9") [without standard table]	0 ~ 150mm (5.9*)
		up to 70mm (2.75") [with optional vacuum table]	
	Weight	up to 5kg (11lbs) [with standard table] / up to 8kg (17.6lbs) [without standard table]	6kg (13,2lbs)
		up to 4kg (8.8lbs) [with optional vacuum table]	
Max printable size (W×D)		483mm (19") ×329mm (12.95")	483mm (19") ×594mm (23.4")
Table height adjustment		PG handle (handle 1.5mm / round)	Automatic
Ink	Туре	UV LED ink (UH21 ink / US11 ink)	
	Ink set	4 colours (K, C, M, Y) / 6 colours (K,C,M,Y, white, varnish)	
	Capacity	220ml ink cartridge (K,C,M,Y, white, varnish)	
	No. of slot	6	
Print resolution		1440/1080/720dpi (Total 3 modes)	
Interface		Ethernet (10BASE-T / 100BASE-TX)	
Power requirements		AC100-120V±10%, 50/60Hz±1Hz	
Operation noise		Standby: 51dB or less / Printing with standard table: 63dB or less /	Standby: 49dB or less / Printing with vacuum table: 69dB or less
		Printing with optional vacuum table: 70dB or less	
Printable environment		Temperature: 20 32°C Humidity: 40 60%RH (non condensing)	
Electrical power consumption		Sleep mode: 20W or less / Ready to print: 40W or less / Operation: 195W or less	Sleep mode: 20W or less /Ready to print: 40W or less / Operation: 300W or less
Dimensions (W×D×H) /Weight		1,188mm (46.8") ×972mm (38.2") ×597mm (23.5") [Front cover closed] / weight: 95kg (209lbs)	1,188mm (46.8") ×1,627mm (64.1") ×604mm (23.8") [Front cover closed] / weight: 130kg (287lbs
		1,188mm (46.8") ×972mm (38.2") ×1,011mm (39.8") [Front cover opened]	1,188mm (46.8") ×1,627mm (64.1") ×1,196mm (47.01") [Front cover opened]
		1,188mm (46.8") ×1,025mm (40.4") ×597mm (23.5") [PG handle cover opened]	
Printer Driver		Bundled	
RIP software		FlexiPRINT SE MUTOH Edition	
Rotary Jig		N/A	Optional
Stand		N/A	Optional

- \* The vacuum table is optional for XPJ-461UF.

- The vacuum lauries between the XP3-401UF / 661UF. RIP software is optional.

  The printer driver is included in the XP3-461UF / 661UF. RIP software is optional.

  Ink adhesion will vary among media type and brand, Individual testing is required in function of your specific application.

  As white ink settles at the bottom of cartridge, please be sure to shake lightly once a day before use.

## **MUTOH**

Mutoh Australia Pty Ltd Unit 19 / 76 Reserve Road, Artarmon NSW 2064 ph: 02 9437 1366 e: sales@mutoh-au.com web: www.mutoh-au.com

Distributed by:



# Xpertuet 461UF | 661UF



# Everything you want in a simple and compact desktop UV LED printer









Print tactile 2.5D graphics such as embossed text, braille, and textured decorations. XPJ-661UF is ideal for premium 2.5D printing grater than 1mm thick XPJ-461UF needs manual adjustment)

### **LED** touch panel




Beautifully designed, intuitive, high visibility electrostatic touch panel for easy to use operation. Supports 8 languages

#### Vacuum table holding media firm



Vacuum table can hold thin media firmly. Control 5 steps of vacuum power directly from the operation Optional for the XPJ-461UF)

#### **Obstacle detection system**







MUTOH EMPLOYEE OF THE YEAR





#### Local Dimming Control (Patent pending)

The XPJ-461UF /661UF are equipped with a newly developed segmented 50mm wide UV lamp. The UV lamp has 6 different sections. Each lamp section can be individually controlled, enabling production of multiple varnish effects in the same print table movement. Gloss, semi-gloss and matte varnish effects can be produced in one table movement for prints combining CMYK + Varnish or White + Varnish. The result is a substantial productivity boost as well as a minimised risk of dust contamination in the glossy printed area.

Ink jetting - varnish smoothing

