



totalimage
SUPPLIES



DISPLAY & GRAPHIC FILM



**ImageDot (SOLVENT, LX, UV)
Clear PET Film 140um**

Removable • Bubble Free • PVC-Free

SKU: ID-PETC140

ImageDot (SOLVENT, LX, UV) Clear PET Film 140um

Removable, Repositionable, and Reusable.

ImageDot is an innovative product that will save time and money when creating and installing wall, window and trade show graphics. The key to its ease of installation is the special dot patterned adhesive which creates air channels that allow for a bubble and wrinkle free installation.

APPLICATION: WALLS & WINDOWS

■ Indoor Signage	■ Point of Sale	■ Graphic Displays
■ Promotional Events	■ Trade Shows and Exhibitions	■ Retail Signage

TECHNICAL DATA

Colour: Clear
Weight: 140um (Thick)
Film: PP Film (PVC-Free)
Ink Technology: Solvent, Latex & UV Inks
Gecko's Toe Pad Design
Non-Adhesive Design with Liner
Bubble-free, Easy & Quick to Install
Removable, Repositionable, and Reusable
No Residual, No Cleaning = Time Saving

Product Specification :	
Film Thickness	140±8µm (0.0055"±0.0003 ")
Total Thickness	190±11 µm (0.0075"±0.0004 ")
Film Weight	170±11 gsm (5.01±0.32 oz/yd ²)
Total Weight	235±14 gsm (6.93±0.41 oz/yd ²)
180°Peel Strength	10~30g/25mm
Release force	< 15 g/25mm
Elongation at Break	>80%
Appearance	Semi Clear
Working Temperature	-20℃ to 80℃(-4°F to 176°F)
Dimensional Stability	≅0.1 in
Shelf Life	Two years

ROLL SPECIFICATION

WIDTH	WEIGHT/ ROLL	ROLL LENGTH	50M
54" 1370MM	170±11 gsm	DIAMETER OF CORE	3 INCH
SKU	ID-PETC1405450	COLOUR	CLEAR