

imagePROGRAF GP-2000/4000

# HIGH VALUE-ADDED OUTPUT FOR GRAPHICS APPLICATIONS



**PANTONE**  
Digital Color

#### **Pantone Digital Color certified**

The imagePROGRAF GP-2000/4000 are Canon's first PANTONE™ calibrated printer<sup>2</sup> for PANTONE PASTEL & NEON GUIDE Coated, in addition to 99% coverage from the PANTONE FORMULA GUIDE Solid Coated<sup>3</sup>.

**Canon**

# imagePROGRAF GP-2000/4000

## SPECIFICATIONS

### Print Head

PF-07

### Technology

FINE (Photolithography Inkjet Nozzle Engineering)

### Print Resolution (Max.)

2,400 x 1,200 dpi

### Line Accuracy\*

±0.1% or less

### Number of Nozzles

18,432 Nozzles (1,536 Nozzles x 12 colors)

### Droplet Size

Minimum 4 Picolitre

### Nozzle Pitch (Head Resolution)

600 dpi x two lines

### Ink Type

**Pigment:** 10 + Fluorescent (MBk/PBK/C/M/Y/GY/R/O/G/V/FP (Fluorescent Pink)

### Ink Tank

#### Shipped with Printer:

GP-2000: 330 ml MBK, 160 ml other colours  
GP-4000: 330 ml per colours

### Ink Supply Method

Tubing System with Sub-tanks

### Nozzle Recovery System

Non-firing Nozzle Detection and Compensation

### Printer Controller

L-COA PRO

### Printer RAM

3 GB

### Hard Drive

500 GB

### Media Feed

Media Feed: 1 Roll, Front-loading, Front output\*  
(\*Option for 2nd roll)  
Cut sheet: Front-loading, Front Output (manual feed using media locking lever)

### Media Width

GP-2000: 152.4–610 mm (6"–24")  
GP-4000: 152.4–1,118 mm (6"–44")

### Printable Margins

**Roll Feed:** All Sides: 3 mm, 0 mm for borderless  
**Cut Sheet:** Apple® AirPrint™: Top: 3 mm, Bottom: 12.7 mm, Side: 3 mm

### Maximum Print Length (Single Page)\*

**Roll Feed:** 18 m

**Cut Sheet:** 2,133.6 mm

### Borderless Printing Widths (Roll Media Only)

#### Recommended:

515 mm (JIS B2), 728 mm (JIS B1)\*, 1,030 mm (JIS B0)\*, 594 mm (ISO A1), 841 mm (ISO A0)\*, 10", 14", 17", 24", 36"\*, 42"\*, 44"\*

#### Printable:

257 mm (JIS B4), 297 mm (ISO A3), 329 mm (ISO A3+), 420 mm (ISO A2), 6", 8", 12", 15", 16", 20", 22", 30", 34", 300 mm, 500 mm, 600 mm, 800 mm\*, 1,000 mm\*, Others (user paper set up for roll paper only)

\* Supported by GP-4000 only.

### Media Cutter

Automatic Horizontal Cutting (Rotary Cutter)

### Media Thickness

0.07–0.8 mm

### Media Internal Diameter Sizes

2" and 3" (Adapters included)

### Maximum Roll Outer Diameter

150 mm or less

### Media Output

Front basket

### Printing Software Utilities

Accounting Manager, Apple® AirPrint™, Device Management Console, Direct Print Plus, Extrakit (Free Layout), Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist Lite for Windows, Quick Utility Toolbox, Canon Print Service, Professional Print and Layout

### Operating System

Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5–v11.x

### Print Language

**Printer:** SGRaster, PDF, JPEG

### Interface

**Standard (Built-in):** USB Hi-Speed (USB B port), 10/100/1000Base-T, Wireless LAN (IEEE 802.11 b/g /n), Direct Printing via USB Memory (USB A port)

### Acoustic Noise

#### Operation:

GP-2000: Approx. 48 dB(A)  
GP-4000: Approx. 49 dB(A)

**Standby:** 35 dB (A) or less

#### Acoustic Power:

GP-2000: 6.5 Bels or less  
GP-4000: 6.6 Bels or less  
(measured on ISO7779 standard)

### Power Supply

AC 100–240 V (50–60 Hz)

### Power Consumption

GP-2000: 84 W or less  
GP-4000: 99 W or less

### Operational Environment

**Temperature:** 15–30°C

**Relative Humidity:** 10–80% (No Dew Condensation)

### Printer Dimensions (W x D x H) and Weight

GP-2000: 1,110 x 984 x 1,168 (Basket Opened)  
102 kg (119kg with Roll Unit)  
GP-4000: 1,593 x 984 x 1,168 (Basket Opened)  
102 kg (119 kg with Roll Unit)

### Package Dimensions (W x D x H) and Weight

GP-2000: Printer with Pallet: 1,324 x 902 x 1,042 mm (125kg)  
**Stand/Basket:** 1,111 x 797 x 223 mm (23 kg)  
GP-4000: 1,820 x 915 x 1,042 mm (178 kg)

### Options

- PosterArtist
- Multifunction Roll System  
GP-2000: RU-23, GP-4000: RU-43
- 2"/3" Roll Holder Set  
GP-2000: RH2-29, GP-4000: RH2-46

### User-Replaceable Items:

- Ink Tank (PFI-2100 (160 ml)/PFI-2300 (330 ml)/PFI-2700 (700ml))
- Print Head (PF-10)
- Maintenance Cartridge (MC-31)
- Cutter Blade (CT-08)

\* Line accuracy repeatability is maximised after a user performs necessary adjustment and under the same environmental conditions.

† The maximum printable length varies depending on the application, OS, and RIP used.

‡ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network client.

1 PANTONE™ is a trademark or registered trademark of Pantone LLC.

2 As of 12 September, 2021 according to professional services performed by Pantone.

3 When using Photo Paper Pro Platinum with imagePROGRAF printer driver at [Poster/Photo (Fluorescent)] [Highest] (600dpi), PANTONE PASTELS & NEONS GUIDE Coated Coverage rate 97%.

When using Photo Paper Pro Platinum with imagePROGRAF printer driver at [Poster/Photo (Fluorescent)] [Highest] (600dpi), PANTONE FORMULA GUIDE Solid Coated Coverage rate 99%

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon recommends you use Canon Media for the best results. Please check media (paper) comparability list to see which variety of paper/media is recommended, available on request.



# Canon

Canon Australia Pty Ltd  
1800 444 199  
canon.com.au/business  
Canon New Zealand Ltd  
0800 222 666  
canon.co.nz/business