## LM4506R



- LED display
- 4 Hot Rollers
- Laminates up to 250mic
- Separate reverse button
- Laminates from I.D. to "A2"
- Robust all metal construction
- Temperature display indicates current, temperature or programmed temperature

- Over-heat (160°c) protection system
- Multi function either hot or cold laminating
- Carrier free operation (No carrier required)
- Adjustable speed and temperature controls
- Ready light (approximately 5 minute warm up)
- Safety sleep mode (after 15 minutes of non use automatically cuts heating)

## **Technical Specifications:**

Product Code & Model Name: ALC- LM450 6R - Pouch Machine 450mm

Top Roll Heat Assist: Up to 160° C Cold Laminating Temp: Up to 50° C Warming-up time: 5 Minutes

Laminating Speed: Variable speed (up to 2100mm/min)

Maximum Laminating Width: ≤ 450mm
Maximum Mounting Thickness: ≤ 1mm

No. of Rollers: 6 silicone rubber rollers (4 hot + 2 cold)

Control system: 8 bit micro-processor Display system: Digital display Power Consumption: 1550W

Assembled Dimensions (mm): 670(L) x 295(W) x 135(H)



Warranty
12 Months Parts Only



Australian RCM Certified



Standard 10amp power AC 240 V/ 50,60 Hz