



SAV 3yr

Features

- 95um monomeric vinyl, 168gsm 2-side PE coated liner and solvent acrylic adhesive;
- Available with grey air-free removable and permanent adhesive, and clear removable and permanent adhesive;
- Suitable for everyday short-term signage and P.O.S applications on flat surfaces;
- Outdoor durability* for up to 3 years;
- Dimensionally stable for easy converting;
- Wide range of temperature adaptability;
- Versatile adhesive suitable for most substrates and removable with heat and/or chemicals;
- Air channel technology for easy installation;
- Printable with latex, UV, eco-solvent and solvent wide format ink systems.

Product Details

Roll size	1.37m x 50m as standard (other sizes available ex production)
Expected durability*	Up to 3 years, unprinted on vertical exterior surfaces.
Printability	Latex, UV, solvent & eco-solvent inkjet.
Removability	Easy to be removed for up to 12 months from installation when installed following correct protocols.
Shelf Life	2 years stored at 23°C and 50% relative humidity.

Graphic application - recommendations	
Surface	Dust free, oil free, smooth, flat, surfaces
Temperature	2°C - 50°C air and substrate
Application method	Dry

Technical Data Sheet

Technical Characteristics

Masterjet SAV 3yr - Gloss White, Grey Removable Adhesive, Air Release Liner

Characteristic	Property
FILM: <ul style="list-style-type: none">Type/Colour/FinishFilm thickness (without adhesive)ElongationTensile StrengthDimensional Stability	<ul style="list-style-type: none">PVC/White/Gloss95 μ \pm 10% (without liner and adhesive)\geq50%\geq20Mpa0.5mm max
ADHESIVE: <ul style="list-style-type: none">TypeColourThicknessInitial TackHolding PowerRelease ForceService Temperature	<ul style="list-style-type: none">Solvent based pressure-sensitive acrylic, removableGrey20\pm2 micron\geq6N/m\geq8N/m50-150g/50mm-15°C to +60°C
LINER: <ul style="list-style-type: none">TypeColourWeight	<ul style="list-style-type: none">2-side PE coated kraft with air channel technologyWhite165gsm \pm 10%